



Winter Products

Prior Antifreeze Arctic Concentrate

| | |
|-----------------------|--|
| Description | Concentrated ethylene glycol based hybrid anti-freeze with a combination of mineral inhibitors and organic ones. Protects against corrosion, overheating and freezing. Typical service life of up to 5 years/ upon recommendation OEM. |
| Application | May be used all the year round in cooling systems of gasoline and diesel engines. This anti-freeze should be diluted with demineralized water before use, in accordance with the ration in the owner's manual. |
| Specifications | Meets the requirements of: MB 325.0 Opel/GM QL 130100 Saab/GM 6901 599 Porsche/Audi/Seat/Skoda TL-774C (G11) |
| Product Safety | For information about product safety view Material Safety Data Sheet 3001. |
| Typicals | Color: BLUE Density at 15 °C, kg/l 1,113 |

Prior-oil is a registered trademark of Eurotex Group Ltd. Produced: Zwijndrecht, Holland by Socaz by order of Eurotex Group Ltd.

12/17/2013
The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.