

## Prior Transmatic ATF-II

<b>Description</b>	Standard automatic transmission fluid for most passenger cars, forklift trucks and buses of European, American or Japanese origin. Also suitable for certain power steering systems, torque converters, change-gearboxes, fluid clutches and non-complicated hydraulic systems.	
<b>Application</b>	This fluid may be used for automatic gearboxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID fluid is required.	
<b>Performance Level</b>	Meets the requirements of: GM Dexron II-D MB 236.7 Allison C4 Caterpillar TO-2 ZF TE-ML 03D/04D/11A/14A/17C MAN 339 Type Z-1	
<b>Typicals</b>	Density at 15 °C, kg/l	0,872
	Viscosity 40 °C, mm <sup>2</sup> /s	43,20
	Viscosity 100 °C, mm <sup>2</sup> /s	8,25
	Viscosity Index	168
	Flash Point COC, °C	198
	Pour Point, °C	-45
	Total Base Number, mgKOH/g	2,6
	Sulphate Ash, %	0,18



Prior-oil is a registered trademark of Eurotex Group Ltd. Produced: Zwijndrecht, Holland by Socaz by order of Eurotex Group Ltd.

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.